


EXPRESS MAIL CERTIFICATE  
"EXPRESS MAIL" LABEL NO: EV066403963US  
Date of Deposit: February 8, 2002

I hereby certify that this paper along with any papers referred to as being attached or enclosed, is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above, addressed to: Attn: Box Patent Application, Assistant Commissioner of Patents, Washington, D.C. 20231.

  
Gretchen King

## APPLICATION FOR

## UNITED STATES LETTERS PATENT

## FOR

## MARINE SEISMIC SOURCE TOWING APPARATUS AND METHOD

**Inventors:** Shyam Kutty  
Stafford, Texas

David McCall  
Alvin, Texas

**Assignee:** Input/Output, Inc.  
12300 Charles E. Selecman Drive  
Stafford, Texas 77477

## BACKGROUND OF THE INVENTION

### Field of the Invention

This invention relates generally geologic surveys and more particularly to an  
5 apparatus and method for producing acoustic signals in a marine environment.

### Description of the Related Art

Seismic exploration is used to determine the presence of subsurface structures in  
earth formations that may contain useful materials such as hydrocarbons. During marine  
seismic operations, a service vessel often tows an acoustic source such as an array of air  
10 guns to generate high-powered acoustic signals. The acoustic energy transmitted by the  
acoustic source radiates generally downwardly into the sea floor and is partially reflected  
back towards the earth's surface by subsurface acoustic impedance boundaries, called  
reflectors, which may exist within the earth. The transducers (*e.g.*, hydrophones), which  
are positioned at or near the water's surface, are used to detect this reflected acoustic  
15 energy. The transducers generate electrical signals proportional to the magnitude of the  
acoustic energy detected.

Typically, the acoustic source consists of an air gun array. A conventional air gun  
array can consist of a plurality of sub-arrays. Each sub-array includes several air guns  
that are placed in a pre-defined spatial relationship to one another. Auxiliary equipment,  
20 such as air gun controllers, is usually positioned immediately above these air guns.  
Additionally, supply lines such as air hoses, electrical power lines and communications  
run between the air guns and equipment on the service vessel. During operation, all the  
air guns of a sub array are activated simultaneously. Upon activation, the air guns release  
individual gas or air bubbles into the water. These bubbles produce acoustical energy that

radiates into the water. The pulse characteristics, such as the frequency, bubble ratio and amplitude, of the overall pressure pulse produced by an air gun subarray is a function of the characteristics of the pressure pulses produced by the individual air guns and the physical arrangement of the air guns in that air gun subarray.

5           Certain seismic survey activities such as those targeting relatively deep subsurface formations or for reservoir mapping require a relatively powerful acoustic signal to obtain the necessary data. While an air gun can be configured to produce this powerful acoustical signal, the overall dimensions and weight of such an air gun can be substantial. It is generally undesirable to use heavy, bulky equipment in a shipboard environment  
10 because of factors such as limited storage capacity, lifting and handling requirements, and difficulties in deployment and retrieval.

          Instead of a single air gun, a relatively powerful acoustic signal can be produced by an air gun cluster. That is, two or more relatively small air guns can be "clustered" to produce an acoustical signal similar to a signal produced by a much larger air gun. To  
15 achieve this affect, each gun in a cluster should be placed sufficiently close together so that their bubbles coalesce in the early stages of the bubble expansion. Conventional methods of clustering air guns include two or three air guns stacked in vertical alignment, *i.e.*, perpendicular to the water surface. Another method uses a triangular relationship wherein a single air gun is superposed over two side-by-side air guns. It is also reported  
20 that air guns have been arranged in horizontal alignment.

          These conventional methods of clustering air guns have a number of drawbacks. First, conventional clustering arrangements having air guns at different depths can produce asymmetric loadings. For example, the net reaction between two air guns can

produce a damaging upward force on an air gun above the two air guns. Moreover, the vertically clustered air guns may need additional equipment to maintain their orientation during towing. More generally, the gun controllers and other auxiliary equipment used in conjunction with conventional air gun arrays can be exposed to the pressure pulse generated by the air gun array during use. Repeated exposure to the jarring affect of the air gun operation can shorten service life or lead to catastrophic failure of this equipment. Further, the supply lines associated with the air guns are frequently exposed to the wave action and contact with the water. This contact can cause, for example, failure in the joints making up the supply lines. In a different aspect, some conventional air gun arrays have profiles that induce substantial drag during towing.

The present invention addresses these and other drawbacks of conventional marine acoustic source systems.

### SUMMARY OF THE INVENTION

The present invention provides a marine acoustic source system having a dense source cluster. The sources, typically air guns, are arrayed in a tandem-like fashion along a horizontal plane beneath the water's surface during towing in a pre-determined direction. Air guns are usually cylindrical in shape and have a connection interface for receiving power, air, or data transmission lines. Each air gun is aligned such that the longitudinal axis of the air gun is orthogonal to the towing direction. The components associated with the air gun cluster include supply lines and auxiliary equipment (*e.g.*, gun controller).

The acoustic source system uses protective tubes and a harness to support and protect the air guns, supply lines and auxiliary equipment. The protective tube has an

elongated axial chamber that substantially houses the span of supply lines between a lead hose and the air guns. The auxiliary equipment is also placed within the chamber. Because this equipment is adjacent and outboard of the air guns, they are protected from the direct blast generated by the air guns. A preferred protective tube includes sleeves, couplings, and connectors. The sleeves are flexible hose-like members that interconnect the couplings. Each coupling has a neck leading to and mating with an air gun. The connectors provide a rugged connection between the air gun and the supply lines. Preferably, the connector has an elbow or angular portion that enables a connection that is substantially co-axial with a supply line.

10 In a preferred cluster arrangement, the air guns are arranged such that the connection interfaces alternate in opposing directions. For example, the air gun array can have a first set of air guns having connection interfaces oriented in a first direction and a second set of air guns having connection interfaces oriented in a second direction. Separate supply lines connect to the connection interfaces of each set of air guns.

15 Likewise, a separate protective tube is provided for each supply line. The use of two protective tubes enhances stability of the air gun array. Moreover, the increased interior space provided by two protective tubes can accommodate a greater number of supply lines. Thus, more air guns can be added to the air gun cluster.

The harness provides the primary mechanical connection through which the air guns are towed through the water. The harness includes collars that are affixed to each air gun, a mating end that connects to the termination, and linking members that connect each of the air guns to the mating end.

During use, an exemplary acoustic seismic source system is deployed behind a service vessel in shallow water. The air gun array of the system is supported by a floatation buoy at a predetermined depth. A tow line extending from the ship is attached to the termination. During towing, the harness, which is connected to the termination, pulls the air gun arrays, and associated air gun clusters, through the water. The harness, thus, takes up the traction forces induced during towing, thereby minimizing the tension forces that would otherwise be imposed on the supply lines. Upon activation, the air guns of a cluster each release individual air bubbles into the water. Because the air guns are in close proximity to one another, the individual air bubbles coalesce into a single bubble that produces the desired acoustical signal.

Thus, the present invention comprises a combination of features and advantages that enable it to overcome the deficiencies of prior systems and methods. The various characteristics described above, as well as other features, will be readily apparent to those skilled in the art upon reading the following detailed description of the embodiments of the invention, and by referring to the accompanying drawings.

It should be understood that examples of the more important features of the invention have been summarized rather broadly in order that detailed description thereof that follows may be better understood, and in order that the contributions to the art may be appreciated. There are, of course, additional features of the invention that will be described hereinafter and which will form the subject of the claims appended hereto.

## DESCRIPTION OF THE FIGURES

For a detailed description of an embodiment of the invention, reference will now be made to the accompanying drawings wherein:

**Figure 1A** schematically illustrates a plan view of a preferred air gun cluster  
5 made in accordance with the present invention;

**Figure 1B** schematically an elevation view of a preferred acoustic source system deployed in water;

**Figure 2** schematically illustrates a plan view of a preferred seismic acoustic source system made in accordance with the present invention;

10 **Figure 3** illustrates a sectional view of a preferred protective tube made in accordance with the present invention;

**Figure 4** illustrates an elevation view of a preferred coupling and connectors made in accordance with the present invention;

15 **Figure 5A** graphically illustrates a relative spacing of a non-cluster type conventional acoustic source array;

**Figure 5B** graphically illustrates the calculated performance of the non-cluster type conventional acoustic source array;

**Figure 5C** graphically illustrates the available frequency range of the non-cluster type conventional acoustic source array;

20 **Figure 5D** graphically illustrates an exemplary spacing of a clustered acoustic source array that employs the teachings of the present invention;

**Figure 5E** graphically illustrates the calculated performance of a clustered acoustic source array that employs the teachings of the present invention;

**Figure 5F** graphically illustrates the available frequency range of a clustered acoustic source array that employs the teachings of the present invention; and

**Figure 6** schematically illustrates an exemplary acoustic source system deployed in a marine environment.

## DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to devices and methods providing rugged and cost-effective seismic source system using one or more dense seismic source clusters. The present invention is susceptible to embodiments of different forms. There are shown in the drawings, and herein will be described in detail, specific embodiments of the present invention with the understanding that the present disclosure is to be considered an exemplification of the principles of the invention, and is not intended to limit the invention to that illustrated and described herein.

Referring initially to **Figure 1A** there is schematically shown an air gun cluster **100** that includes a plurality of air guns **102a-d**. The air guns **102a-d** are spatially oriented to produce an acoustical signal substantially similar to a signal produced by a single air gun. The cooperative action of the air guns **102a-d** is achieved by placing the air guns **102a-d** in sufficiently close physical proximity such that the individual bubbles generated by each air gun **102a-d** coalesce into a single air bubble in the early stages of the bubble expansion. An air gun "cluster" should be contrasted with an air gun array or sub-array. In an air gun array or sub-array, the individual bubbles generated by each air gun do not generally coalesce into a single air bubble in the early stages of the bubble expansion. As will become apparent, the teachings of the present invention will enable a greater number of air guns in a cluster as compared with conventional air gun



arrangements. While four air guns, which is a particularly preferred arrangement, are depicted in **Figure 1A**, it should be understood that greater or fewer air guns may be used. For example, the air guns shown in phantom illustrate an exemplary extension of the cluster **100** or another cluster having two air guns.

5           The optimal separation distance between air guns **102** in a cluster **100** depends on the volume of the guns, the operating pressure, and the ambient hydrostatic pressure. This optimal separation distance  $D_c$ , or range of separation, can be calculated with the following Equation A:

10           Equation A:           
$$D_c = 2 \left( \frac{3}{4\pi} \frac{P}{P_o} V \right)^{1/3} \pm 50\%$$

In Equation A:

$D_c$  = Center-to-center distance between guns in a cluster

$P$  = Gun absolute pressure (psia)

$P_o$  = Ambient absolute pressure (psia)

$V$  = Volume of single gun in the cluster

15           For example, a simple cluster may have two air guns each having 150 in<sup>3</sup> volume capacity and an absolute pressure of 2000 psig. Further, this cluster may be deployed at a depth of 6 meters. Thus:

$V = 150 \text{ in}^3$

$P = 2014.7 \text{ psia } (2000 \text{ psig} + 14.7 \text{ psi})$

$P_o = 23.4 \text{ psia } (14.7 \text{ psi} + (6 \text{ m})(1.458 \text{ psi/m}))$

25           With the above values entered as follows:

$$D_c = 2 \left( \frac{3}{4\pi} \frac{2014.7 \text{ psia}}{23.4 \text{ psia}} 150 \text{ in}^3 \right)^{1/3} \pm 50\%$$

Executing the above calculation shows that the optimal center-to-center distance  $D_c$  between air guns is 29.08 inches or .74 meters  $\pm$  .37 meters. It will be appreciated, therefore, that Equation A provides a range of values for separation distances that will promote the clustering effect; *i.e.*, approximately 0.37 meter to 1.11 meters. Stated more generally, the term “ $(D_c - (D_c)(50\%))$ ” provides an approximate lower limit and the term “ $(D_c + (D_c)(50\%))$ ” provides an approximate upper limit. Thus, Equation A provides a general guideline as to the optimal relative spatial arrangement of the air guns **102**.

It should be understood, however, that the clustering effect may still be achieved if the relative spacing of the air guns **102** is outside the optimal range. As a general guideline, for air guns to act independently, that is, to not interact as in a cluster, the separation distance  $D_s$  between guns should be greater than the value provided by the following Equation B:

$$D_s \geq .62 \cdot V^{1/3} \text{ meters}$$

In Equation B:

$D_s$  = Minimum separation distance in meters  
 $V$  = Volume of largest operative air gun in  $\text{in}^3$

For example, a given array may have two elements: a two150  $\text{in}^3$  air gun cluster and a single 150  $\text{in}^3$  gun to be fired at 2000 psig. An “operative air gun” can include a single air gun. Moreover, an “operative air gun” can also include two or more air guns that, during operation, act as a single air gun. In either case, the elements can be considered to have a reference point, such as a center, for establishing relative positioning. In the above example, the volume of the operative air guns, the two-by-150  $\text{in}^3$  cluster, is 300  $\text{in}^3$ , which is greater than the volume of the single air gun. Thus:

$$D_s \geq .62 (300 \text{ in}^3)^{1/3} \text{ m}$$

$$D_s \geq 4.2 \text{ m}$$

5 Therefore, to prevent the 2 x 150 in<sup>3</sup> air gun cluster from interacting with the single 150 in<sup>3</sup> gun, the two elements should be separated by a minimum center-to-center distance of 4.2 meters. Stated differently, to induce a clustering effect, two or more elements should be placed no greater than  $D_s$ , where  $D_s = 0.62 \cdot V^{1/3}$  meters. Equations **A** and **B** are general guidelines and employ measurement units (*e.g.*, meters or inches) that generally conform to conventional industrial use. It should be understood that the coefficients and mathematical relationships may vary depending on the particular measurement units used or a given application. For example, the coefficient "0.62" may be as low as 0.50 or as high as 0.75. Furthermore, because Equations **A** and **B** are based on empirical relationships, these equations may be subject to refinements based on newly developed technologies. Thus, the present invention is not limited to the precise relationships set forth in Equations **A** and **B**. The state of the art as pertaining to mechanics of air gun clustering is illustrated in "Signature and Amplitude of Linear Air Gun Arrays," Nooteboon, J. J., Paper presented at the EAGE Conference, June, 1976, Hague; and in "Compact sleeve-gun source arrays," by P.M. Fontana and T.A. Haugland, Geophysics, Vol. 56, No. 3 (March 1991), both of which are hereby incorporated herein by reference for such teachings.

An exemplary air gun **102b** is generally cylindrical and includes a head **103a**, a tail **103b**, a port **103c**, and a connection interface **103d**. An exemplary connection interface **103d** is formed on the head **103a** and can include one or more ports, valves, or plugs for receiving power, hydraulic fluid, high-pressure air, or data transmission lines

having metal or fiber-optic wires. The connection interface **103d** is connected to a supply line **104** via intermediate lines discussed below. The port **103c** is an aperture through which high-pressure fluid (*e.g.*, air, gas, or water) selectively exits the air gun **102**. For convenience, a longitudinal axis of the air gun **102b** is labeled as **A-A**. The supply line **104** and auxiliary equipment **106** cooperate to energize and operate the air guns **102a-d**. The supply line **104** collectively refers to power lines, air hoses, analog and/or digital data transfer lines, and other similar lines. The auxiliary equipment **106** collectively refers to equipment such as gun controllers, acoustic positioning devices, pressure sensors and depth measurement devices. These are only exemplary of the types of equipment that could be used in conjunction with air guns **102**.

It should be understood that the present invention is not limited to air guns but can be advantageously applied to other known acoustic sources such as water guns, gas guns, and marine vibrators. Indeed, the present invention may be directly applicable to any acoustic sources that may be arranged in a cluster fashion to enhance the quality and efficiency of the acoustical energy produced by the acoustic sources.

Referring now to **Figures 1A** and **1B**, the air guns **102a-d** of the air gun cluster **100** have a preferred spatial relationship relative to the water surface **110**, the direction of towing **T**, and each other. The air guns **102a-d** are arranged generally along a horizontal plane **H-H** that is substantially parallel with the water surface **110**. By maintaining the air guns **102a-d** at a substantially common depth, the forces associated with air gun activation will be more symmetric than the forces associated with air guns positioned at different depths. It will be understood that the term “water surface” refers to a nominal condition wherein the water surface is relatively flat and unperturbed by, for example,

inclement weather. Accordingly, the "water surface" or "a plane parallel to the water surface" is used synonymously with the term "horizontal plane." Further, the ports **103c** of the air guns are aligned along substantially the same plane **B-B**. Plane **B-B** is substantially vertical (*i.e.*, perpendicular to the water surface). This alignment of the

5 ports **103c** promotes the coalescence of the air bubbles created by the high-pressure fluid (*e.g.*, air) discharged from the ports **103c**. Where more than one cluster is used, it is also preferred that the ports of the air guns in each such cluster also be aligned in substantially parallel planes; *i.e.*, planes parallel to plane **B-B**. Of course, the ports of successive air gun clusters need not be in identical planes because of differences in air gun sizes and

10 configurations. In addition to a generally uniform depth, the longitudinal axes **A-A** of the air guns **102a-d** are aligned substantially orthogonal to the direction of towing **T**. In a preferred arrangement, the axes **A-A** are also parallel with the horizontal axis **H-H**. From the plan or top view of **Figure 1A**, it can be seen that air guns **102a-d** are thereby placed in a side-by-side or tandem-like configuration. In an alternate embodiment that is not

15 shown, the longitudinal axes of the air guns are aligned substantially orthogonal to the direction of towing and also substantially orthogonal to the horizontal axis. When this alternate embodiment is used, the air gun tail **103b** (**Fig. 1A**) is directed upwards and the air gun head **103a** (**Fig. 1A**) is directed generally downward. In this alternate embodiment, the plane along which the air gun ports are aligned (corresponding to plane

20 **B-B** in **Figure 1A**) will be parallel to the water surface. It should be appreciated that these side-by-side configurations enable a more dense packing of the air guns **102a-d** as compared, for example, to a configuration wherein the air guns are laid end-to-end. Referring now to **Figure 1B**, the air guns **102** are positioned at a pre-defined depth **D**

below the water surface **110**. As is known, the air guns **102** must be submerged in order to produce an effective air bubble. Often, depth **D** is approximately one meter or greater. The depth **D**, however, can be greater or less depending on the particular application. It would be apparent to one skilled in the art as to the proper depth **D** at which the air guns

5 **102** should be submerged for a given application.

Referring now to **Figure 2**, there is shown a preferred acoustic source system **200** that incorporates a preferred air gun cluster **100**. The air gun cluster **100** includes air guns **102a-d** arranged as shown in **Figures 1A-B**. The acoustic source system **200** includes a tow line **210**, a termination **220**, a harness **230**, lead hoses **240**, and protective tubes

10 **250a,b**. The acoustic source system **200** may be suspended from a floatation device **112** (**Figure 1B**). The supply lines **104a,b** are positioned inside the hoses **240** and protective tubes **250a,b** and thereby protected from the drag forces associated with towing. Likewise, the auxiliary equipment **106** is also located inside the protective tubes **250a,b** for protection against the elements and the shock and vibration of air gun operation.

15 Advantageously, the placement of the auxiliary equipment **106** next to the axial ends of the air guns **102a-d**, rather than above the airguns, also minimizes the percussive shock encountered by the auxiliary equipment during air gun operation.

The source system **200** preferably minimizes the overall bundle size of the supply lines **104** leading to the air guns **102a-d**. For example, a first supply line may be used to

20 connect with a first set of air guns, and a second supply line may be used to connect to a second set of air guns. Thus, two smaller supply line bundles are used in lieu of one large supply line bundle. Referring back to **Figure 1A**, in a preferred arrangement, a first set of air guns **102a,c,e** have ports **103d** pointed in a first direction and a second set of air

guns **102b,d,fb** have ports **103d** pointed in a second direction. Thus, a first supply line **104a** connects to the first air gun set **102a,c,e** and a second supply line **104b** connects to a second air gun set **102b,d,f**. The first air gun set **102a,c,e** and the second air gun set **102b,d,f** are preferably intermeshed such that ports **103d** of consecutive air guns **102a-d** point alternatively in the first and second directions. It should be understood that the ports **103d** need not point in opposing directions and that the ports **103d** can point in more than two directions. It will be appreciated that the use of multiple supply lines **104** increases the capacity of the power and data transmission of the acoustic source system and therefore enables the use of additional air guns in the cluster **100**.

Referring now to **Figure 2**, the acoustic source system **200** uses the tubes **250a,b** to protect the supply lines **104** and auxiliary equipment **106** from exposure to the damaging effects of the marine environment. The tubes **250a,b** are substantially flooded with water during use and maintain the supply lines **104** and auxiliary equipment **106** in an environment of relatively slow or non-moving water. Thus, the tubes **250a,b** reduce the amount of drag imposed on the supply lines **104** and auxiliary equipment **106** as the acoustic system **200** is towed through the water. The tubes **250a,b** are positioned outboard of the air guns **102a-d** in a generally parallel relationship. Referring now to **Figure 3**, each tube **250a,b** includes an elongated chamber **258** in which the supply lines **104** and auxiliary equipment **106** may be housed. For example, the supply lines **104** run axially along the chamber **258**. The tubes **250a,b** may be molded as a single piece or constructed with two or more components. Because tubes **250a** and **230b** are essentially identical, the following description will, for convenience, refer to tube **250**. A preferred tube **250** includes couplings **252**, sleeves **254**, and connectors **256**.

Referring now to **Figures 3 and 4**, the coupling **252** provides an access way from the chamber **258** to the air guns **102a-d**. A preferred coupling **252** includes a neck **260** and a barrel portion **262**. The neck **260** has an interior space **253** for receiving the connectors **256** and is adapted to house or mate with the air gun **102**. Referring now to **Figure 4**, the coupling **252** may be formed of mating shells **264a,b**. Clamps **259** may be used to bind the shells **264a,b** together. Such a split shell configuration facilitates field repair and maintenance by allowing quick and convenient access to the supply lines **104**, equipment **106**, and the air gun **102**. The coupling **252** may be molded or formed by other known means. Alternatively, a flange (not shown) may be used in conjunction with thread fasteners or quick disconnect devices to hold the shells **264a,b** together. Such fastening arrangements are known in the art and would be apparent to one skilled in the art.

In other embodiments, the tubes may include one or more fluid tight compartments. These compartments may also include a buoyant fluid such as kerosene or air. These compartments may be selectively filled to achieve a desired buoyancy for the system **200**.

Referring now to **Figures 3 and 4**, the connectors **256** provide a rugged connection between the supply lines **104** and the air guns **102**. The supply lines **104b** run generally axially within the tube chamber **258**. The air gun connection interface **103d**, however, is oriented generally perpendicular to the supply lines **104**. To minimize the bending and need for sharp radii in the supply lines **104**, the connector **256** has an axial portion **266** that mates with the air gun plug **103d** and an angular portion **268** that mates with the supply lines **104**. Thus, the connectors **256** enable, for example, electrical lines



and air hoses, to establish electrical, data, and power connections to air guns **102a-d** without bending.

Referring now to **Figure 3**, the sleeves **234** provide a resilient and flexible connection between adjacent couplings **252** and with the lead hoses **240a,b**. The sleeves **254** are a hose-like member that may be formed natural or synthetic rubbers or other materials suitable for marine environment. The sleeves **254** slide over the ends of the coupling barrel **262** to form a compressive fit between the sleeve **254** and the barrel **262** of the coupling **252**. Additionally, a clamp **272** that surrounds the sleeve **254** and the coupling **252** can also be used.

To provide stability to the air guns **102a-d**, a bridge **290** may be used to fasten the air gun tail **102b** to an adjacent sleeve **254**. The bridge **290** may be a clamp or two arms that support the air gun at the tail **102b**. The bridge **290** need not be a rigid connection as, for example, used with rungs of a ladder. Rather, the bridge **290** may simply prop up the air gun **102**, which is effectively cantilevered from the coupling **252**. For example, the bridge **290** can allow limited movement along the A-A axis while substantially preventing the air gun **102** from rotating about the coupling **252**.

Referring now to **Figure 2**, the tow line **210**, a termination **220**, a harness **230**, and lead hoses **240** of acoustic source system **200** make up the support structure for towing the preferred air gun cluster **100** and protective tubes **250a,b** through the water.

In an exemplary arrangement, the tow line **210** extends from a service vessel (not shown) or other vehicle (*e.g.*, a paravane) and connects to the termination **220**. The termination **220** acts as a tow point and can also provide a central conduit through which supply lines **104** and other equipment can be consolidated. The lead hoses **240a,b** protect and guide

the span of supply lines **104a,b** that extend between the termination **220** and their respective tubes **250a,b**.

Referring now to **Figure 3**, the harness **230** provides the primary mechanical connection through which the air guns **102a-d** are towed through the water. The harness  
5 **230** includes collars **232**, links **234**, and a mating end **236** that connects to the termination **220**. Each of the collars **232** are fastened about the air guns **102a-d** using known means such as threaded fasteners, clamps, rivets, or quick disconnect devices. The links **234** connect each of the collars **232**, either directly or indirectly, to the mating end **236** that engages the termination **220**. The links **234** may be formed of chains, cables, belts, rope,  
10 wire, and other similar lines. It should be understood that while two sets of collars **232** and links **234** are shown, greater or fewer sets of the same may be used for different applications.

It should be noted that there are two mechanical connections between the air guns **102a-d** and the termination **220**. The first connection includes the couplings **252**, sleeves  
15 **254**, and the lead hose **250**. The second connection is the harness **230**. It will be appreciated that individual air guns can weigh several hundreds of pounds. Thus, the device used to tow the air guns will encounter significant stresses during use. It is therefore preferred that the harness **230** is configured such that it pulls the air guns **102a-d** through the water without inducing traction in the first described connection. For  
20 example, the lead hoses **240** should be provided with sufficient slack such that the harness **230** transmits the towing force from the termination **220** to the air guns **102a-d**.

Referring now to **Figure 5A-F**, there are shown in graphical format the results of analyses using known computer modeling techniques. Referring initially to **Figure 5A**,

there is shown a conventional arrangement of four air guns **500** each having a 300 CC capacity. The port-to-port distance **502** between the air guns is about 2.4 meters. Referring briefly to **Figure 3**, an exemplary port is identified with numeral **103c**. Computer modeling indicates, as shown in **Figure 5B**, that the peak bubble ratio (P/B) for this arrangement is about 7.7. As is known, P/B ratio provides an indication of the efficiency of an air gun array. Moreover, as shown in **Figure 5C**, the low-end frequency **504** is about 8 HZ. Applying the teachings of the present invention as shown in **Figure 5D**, the same air guns **500** are arranged such that the port-to-port distance **506** between the air guns is about 1 meter. It should be understood that the air gun arrangement shown in **Figure 5D** is merely a generic software rendered picture that shows relative spacing between the air guns and other aspects of air gun orientation. Referring now to **Figures 5E,F**, it is predicted that the P/B ratio increases to 31.5 and the available low-end frequency **508** is extended to 4.5 HZ. Thus, by using a clustering arrangement in accordance with the present invention, at least (1) the efficiency of the air gun array is significantly enhanced; and (2) the available frequency is extended.

Referring now to **Figure 6** there is shown an exemplary marine seismic survey system **600** deployed in conjunction with a service vessel **602**. The survey system **600** is connected to the service vessel **602** via a tow line **604**. The tow line **604** can include towing cables, supply lines and other lines enabling the transfer of data, power and hydraulic fluids (*e.g.*, air) between the service vessel **602** and the survey system **600**. The service vessel **602** can also include processors **606** in communication with the survey system **600**. The processors **606** can be configured to execute known tasks such as control system operations and record data. The survey system **600** includes a acoustic

source array **610**. The array **610** is further made up of sub arrays **620**. Each sub array **620** includes one or more acoustic source systems **200**, each of which have air gun clusters **100**. The array **610** presents a minimal profile with respect to the direction of towing. This minimal profile can, for example, reduce fuel consumption by the service vessel while allowing increased towing speed. It should be understood that **Figure 6** illustrates an exemplary survey system arrangement. Other arrangements can include greater or few arrays, sub arrays, or air gun clusters. Moreover, several rows of arrays may be simultaneously deployed by the service vessel.

Presuming familiarity with the above-described features, the following discussion regarding the operation of the preferred acoustic source system dispenses with the numerals associated with these features. During an exemplary marine seismic survey campaign, the acoustic source system is deployed by a service vessel in the waters of a geographical area of interest. The source system is towed beneath the water behind the vessel via a tow line leading from the ship to the termination. Similarly, supply lines for transmitting hydraulic fluid, electrical power, air and data extend from the vessel to the source system. The acoustic source system can include an air gun array having one or more subarrays. Each subarray can further include an air gun cluster. The air gun array is suspended from a suitable floatation buoy at a predetermined depth.

During towing, the harness, which is connected to the termination, pulls the air gun cluster through the water. Because the harness takes up the traction forces induced during towing, the supply lines are not subject to such tension forces. Additionally, the protective tubes further protect the supply lines by limiting the damage that occurs as hoses or wires are dragged through the water. Upon activation, the air guns of a cluster

each release individual air bubbles into the water. Because the air guns are in close proximity to one another, the individual air bubbles coalesce into a single bubble that produces the desired acoustical signal. Furthermore, because the auxiliary equipment is outboard of the air guns, this equipment is not directly exposed to the shock associated with the air gun operation.

The foregoing description is directed to particular embodiments of the present invention for the purpose of illustration and explanation. It will be apparent, however, to one skilled in the art that many modifications and changes to the embodiment set forth above are possible without departing from the scope and the spirit of the invention. It is intended that the following claims be interpreted to embrace all such modifications and changes.